

FEATURES

ARTICLE: OHM					IN-01260/2012 IN-01312/2012 IN-01492/2012-3 IN-01829-2012-1 Document 11351 Document 11352 Document 11353		
FACE FABRIC COMPOSITION : 60%CO 40%PP TOTAL COMPOSITION : 50%CO 25%PP 25%PES							
WIDTH: 140	+4cm.	WEIGHT: 480	gr/m ² . ±5%	672	gr/ml.±5%	WARP	WEFT
ESTADISTIC NUMBER: 52114990 USA : 5211410020							
SEAM SLIPPAGE RESISTANCE (mm) EN ISO 13936/2:2004; Load Method(180 N) Seam Slippage (mm)					2.2	2.3	
ABRASION RESISTANCE (End point) EN ISO 12947-2:1998					42.000		
ABRASION RESISTANCE (Change of aspect: 3000 ciclos) EN ISO 12947/4:1998 and EN 14465:2003 (Annex A) Colour Degradation on grey scale (From de 1 worst to 5 best)					4/5		
PILLING RESISTANCE EN ISO 12945/2:2000; Modified Martindale Method (2000 and 7000 cycles) Pilling index (From 1 worst to 5 best)					4		
ASSESSMENT OF IGNITABILITY EN 1021-1:2006 (cigarette test)					PASSED		
EN 1021-2:2006 (match test)					---		
LIGHTFASTNESS EN ISO 105-B02:1998 y EN ISO 105 B02/A01:2002 Colour degradation on blue sale (From 1 worst to 8 best)					5		
COLOUR FASTNESS TO RUBBING EN ISO 105-X12:2002 Degradation and loss of colour on grey scale (From 1 worst to 5 best)			DRY		---		
			WET		---		
COLOUR FASTNESS TO DOMESTIC AMD COMERCIAL LAUNDERING (30°) EN ISO 105-C06:1997 Colour degradation on grey scale (From 1 worst to 5 best)					---		
DIMENSIONAL CHANGE IN DOMESTIC WASHING AND DRYING (%) EN ISO 3759:2008 – EN ISO 6330:2000 – EN ISO 5077:2008					-3%	-2%	
SOILING AND CLEANABILITY FORD FLTM BN 112-08:2005 (From 1 worst to 5 best)					---		
WATER REPELLENCY (HYDROPHOBIA) Spray Test AATCC22 (From 0 worst to 100 best)					70		
OIL REPELLENCY (OLEOPHOBIA) AATCC 118:2002 (From 1 worst to 8 best)					5-6		
<div><div></div><div></div><div></div><div></div></div>							

NOTES: REPELLENCE PROTECTION

ATTENTION: WHEN CONFECTIONING OR WASHING THE SOFA COVER WITH VELCRO PLEASE ATTACH A PROTECTIVE CLOTH OR STRIP OVER THE VELCRO TO AVOID DAMAGE TO THE FABRIC.

Cotton is a material whose fibres tend to shred. This effect is part of the fabric's nature