

Client: Crevin, s.a.
Pol.Ind.Santa Margarita I
C/Llobregat, 21
08223 Terrassa (BCN)
Spain

Entry No: 68888

Date received: 13/02/2015

Client's Description: Sample of fabric: Urus-FR (Yarn)

TEST REPORT

Test Required: Flammability in accordance with The Furniture and Furnishings (Fire) (Safety) Regulations 1988 and Amendments Schedule 4 Part I and Schedule 5 Part I

Pre-treatment: None

Conditioning: A minimum of 96 hours at 50 +/- 20% Relative Humidity, 20 +/- 5° C

Method of Test: BS 5852 : Part 1 : 1979

Date of Test: 03/03/2015

The following test results relate only to the ignitability of the combination of materials under the particular conditions of test; they are not intended as a means of assessing the full potential fire hazard of the materials in use.

Ignition Source	Observations	Result
0 (cigarette)	No flaming or progressive smouldering was observed within one hour of placement of the cigarettes.	PASS
1 (butane flame)	Flaming ceased within the specified two minute period after removal of the butane flame and no progressive smouldering occurred.	PASS

Note: 20-22 kg/m³ non fire retardant polyurethane foam was used as the filling.

Comments

On the basis of the tests carried out this sample of fabric meets the requirements of Schedule 4 Part I and Schedule 5 Part I.

-----End of Document-----

This is hereby certified to be a correct return of the tests made of the items referred to herein.



D. Brockbank.
Materials Testing Manager
4th March 2015

- ❖ Unless instructed otherwise by the client sample remnants will be disposed of after 28 days
- ❖ Test marked (*) in this certificate are not included in the UKAS Accreditation Schedule for this Laboratory.
- ❖ Opinions and interpretations expressed herein are outside the scope of UKAS accreditation.
- ❖ This Certificate relates only to the sample received and, unless that sample has been drawn by the staff of this laboratory, or its agent, and endorsed accordingly, any application of the result to a bulk quantity or other material is entirely the responsibility of the client.



Client: Crevin, s.a.
Pol.Ind.Santa Margarita I
C/Llobregat, 21
08223 Terrassa (BCN)
Spain

Entry No: 68888-02

Date received: 13/02/2015

Client's Description: Sample of fabric: Urus-FR (Yarn)

TEST REPORT

Test Required: Flammability BS 7176 Low Hazard
Pre-treatment: None
Conditioning: A minimum of 24 hours at 50 +/- 5% Relative Humidity, 23 +/- 2° C
Method of Test: BS EN 1021-1: 2006 – smouldering cigarette
BS EN 1021-2: 2006 – match flame equivalent
Date of Test: 04/03/2015

Ignition Source	Observations	Result
Smouldering cigarette	No flaming or progressive smouldering was observed within one hour of placement of the cigarettes.	PASS
Match flame equivalent	Flaming ceased within the specified two minute period after removal of the butane flame and no progressive smouldering occurred.	PASS

Note: A 35 kg/m³ CMHR foam (Carpenters RX36-125) which meets the requirements of Annex A of BS 7176 was used as the filling


The above results relate only to the ignitability of the combination of materials under the particular conditions of test; they are not intended as a means of assessing the full potential fire hazard of the materials in use.

Comments

BS 7176 : 2007 + A1 : 2011 relates to labelling of furniture. If an item of furniture was manufactured from a composite of the fabric and foam tested above then it would comply with the low hazard category flammability requirements provided that it was tested every 2.500 units or once per month as required by Para 5 of BS 7176.

-----End of Document-----

This is hereby certified to be a correct return of the tests made of the items referred to herein.



D. Brockbank.
Materials Testing Manager
4th March 2015



- ❖ Unless instructed otherwise by the client sample remnants will be disposed of after 28 days
- ❖ Test marked (*) in this certificate are not included in the UKAS Accreditation Schedule for this Laboratory.
- ❖ Opinions and interpretations expressed herein are outside the scope of UKAS accreditation.
- ❖ This Certificate relates only to the sample received and, unless that sample has been drawn by the staff of this laboratory, or its agent, and endorsed accordingly, any application of the result to a bulk quantity or other material is entirely the responsibility of the client.



Client: Crevin, s.a.
Pol.Ind.Santa Margarita I
C/Llobregat, 21
08223 Terrassa (BCN)
Spain

Entry No: 68888-01

Date received: 13/02/2015

Client's Description: Sample of fabric: Urus-FR (Yarn)

TEST REPORT

Test Required: Flammability

Pre-treatment: None

Conditioning: A minimum of 24 hours at 50 +/- 5% Relative Humidity, 23 +/- 2°C

Method of Test: BS EN 1021-1:2006 – smouldering cigarette
BS EN 1021-2:2006 – match flame equivalent

Date of Test: 04/03/2015


Ignition Source	Observations	Result
Smouldering cigarette	No flaming or progressive smouldering was observed within one hour of placement of the cigarettes.	PASS
Match flame equivalent	Flaming ceased within the specified two minute period after removal of the butane flame and no progressive smouldering occurred.	PASS

Note: A 35 kg/m³ CM foam (Carpenters RX36-125) was used as the filling


The above tests relate only to the ignitability of the combination of materials under the particular conditions of test; they are not intended as a means of assessing the full potential fire hazard of the materials in use.

-----End of Document-----

This is hereby certified to be a correct return of the tests made of the items referred to herein.



D. Brockbank.
Materials Testing Manager
4th March 2015



- ❖ Unless instructed otherwise by the client sample remnants will be disposed of after 28 days
- ❖ Test marked (*) in this certificate are not included in the UKAS Accreditation Schedule for this Laboratory.
- ❖ Opinions and interpretations expressed herein are outside the scope of UKAS accreditation.
- ❖ This Certificate relates only to the sample received and, unless that sample has been drawn by the staff of this laboratory, or its agent, and endorsed accordingly, any application of the result to a bulk quantity or other material is entirely the responsibility of the client.



**Test report Martindale Abrasion
NS-EN 12947-2 :1999**

Client Crevin,s.a. Pol. Ind. Santa Margarita I C/ Llobregat, 21 08223 TERRASSA Spania		Product URUS-FR	
Client's reference Pep Margarit		Product specification - tested object	
Date 20.05.2015		Date of receipt, tested object 12.05.2015	R-no. R15456
		Test completed date 20.05.2015	Rev. no. / Rev. date 0/

Manufacturer:

Composition:

Pressure : 795 g(12 kPa) Type felt: Woven

The samples are conditioned at 20 degrees C and 65 % relative humidity for 18 hours

Determination of the abrasion resistance of textiles on a Martindale testmachine according to NS-EN 12947-2. Circular specimens of fabric are abraded against a reference fabric.

For woven fabrics the resistance to abrasion is estimated by number when two threads are broken.

For pile fabrics the resistance to abrasion is estimated by the number of cycles when the pile is fully worn off. For nonwovens the resistance to abrasion is estimated by the number when there is a hole of 0.5mm.

The average of four samples gives the results.

<p>Sample no. 1: 34000</p> <p>Sample no. 2: 34000</p> <p>Sample no. 3: 34000</p> <p>Sample no. 4: 34000</p> <p>Average 4 Samples: 34000</p>
--

Comments:

Deviations from test standards: 3 Yarns breaking



Bård Vestre
Manager

**Test report - Abrasion Resistance
EN ISO 12947/4:1998, EN 14465:2003
(Shade change 3000 cycles)**

Client Crevin,s.a. Pol.Ind.Sta. Margarita c/ Llobregat, 21 08223 Terassa (Barcelona) Spania		Product URUS FR Product specification - tested object	
Client's reference Pep Margarit		R-no. R15385	
Date 19.02.2015	Date of receipt, tested object 16.02.2015	Test completed date 18.02.2015	Rev. no. / Rev. date 0/

Manufacturer:

Composition: 49% PP, 33% PES, 18% CO

Type felt: Woven

The samples are conditioned at 20 degrees C and 65 % relative humidity for 18 hours

Results:

3000 Cycles: 4

Comments:

Deviations from test standards:



Bård Vestre
Manager

**Test report Textile Pilling
NS-EN ISO 12945-2 :2000**

Client Crevin,s.a. Pol.Ind.Sta. Margarita c/ Llobregat, 21 08223 Terassa (Barcelona) Spania		Product URUS-FR Product specification - tested object	
Client's reference Pep Margarit		R-no. R15385	
Date 19.02.2015	Date of receipt, tested object 16.02.2015	Test completed date 19.02.2015	Rev. no. / Rev. date 0/

Manufacturer:

Composition:

Loading Mass : 415 g

Type felt: Woven

The samples are conditioned at 20 degrees C and 65 % relative humidity for 18 hours

Numerical assessment of pilling is done on a Martindale abrasion tester according to NS-EN ISO 12945-2. The samples are given a multi-directional movement and are rubbed against fabric of 100% wool (SM 25). 3 samples are used and they are examined on 500, 1000, 2000 and 5000 rubs. The average on each stage is reported as the pilling grade.

The samples are examined on a scale from 1-5 where 5 is best. Examined by 1 person.

Results: 2000 Cycles:5
 7000 Cycles:5

Comments:

Deviations from test standards: Intervals 2000,7000



Bård Vestre
Manager

**Test report Resitance against rubbing
EN ISO 105 X12**

Client Crevin,s.a. Pol.Ind.Sta. Margarita c/ Llobregat, 21 08223 Terrasa (Barcelona)		Product URUS-FR	
Client`s reference Pep Margarit		Product description	
Date 19.02.2015		Revision nr./Revision date 0/	R-no. R15385
		Date of receipt, tested object 16.02.2015	Test completed date 18.02.2015

MANUFACTURER:	
COMPOSITION:	

A white piece of fabric is rubbed against the testspecimen.
Two tests are performed: one dry and one wet.
The grade goes from 1 to 5 with 5 as the best.

RESULT DRY:5

RESULT WET:5

Comments:

Deviations from test standards:



Bård Vestre
Manager

INFORME DE ENSAYO / TEST REPORT

Nº **2017AN0106**

FECHA RECEPCIÓN
DATE OF RECEPTION

19/01/2017

SOLICITANTE / APPLICANT

CREACIONES DE VELOURS INDUSTRIALES,
SA (CREVIN)
C/ LLOBREGAT, 21
ES-08223 Terrassa
Barcelona

Att. PEP MARGARIT

FECHA ENSAYOS
DATE TEST

Inicio / Starting: 19/01/2017
Finalización / Ending: 30/01/2017

DESCRIPCIÓN
E IDENTIFICACIÓN
DE LAS MUESTRAS

DESCRIPTION AND
IDENTIFICATION OF
SAMPLES

MUESTRAS REFERENCIADAS / SAMPLES REFERENCED:

-“URUS-FR”.

ENSAYOS
REALIZADOS

TESTS CARRIED OUT

- SISTEMA DE ENSAYO Y CLASIFICACIÓN PARA LA EVALUACION DE LA RESISTENCIA AL CIGARRILLO EN COMBUSTION DE LOS COMPONENTES DE MUEBLES TAPIZADOS
TEST AND CLASSIFICATION SYSTEM FOR CIGARETTE IGNITION RESISTANCE OF COMPONENTS OF UPHOLSTERED FURNITURE

ENAC es firmante del Acuerdo Multilateral (MLA), (Acuerdo de Reconocimiento Mutuo MRA) de la European Cooperation for Accreditation (EA) y de la International Laboratory Accreditation Cooperation (ILAC), en materia de ensayos. / ENAC is a signatory to the Multilateral Agreement (MLA), (MRA Mutual Recognition Agreement) of the European Cooperation for Accreditation (EA) and the International Laboratory Accreditation Cooperation (ILAC), in testing.

SE ADJUNTAN
ATTACHED

MUESTRA(S)
SAMPLE(S)

LACRADA(S)
SEALED

PÁG.
PAGE

1

DE
OF

5