






















# crevin

## BORA BORA (IMP)

in/out



Characteristics 	Specifications 	Care 	Ignitability 	Environment 
<p><b>Total composition</b> 80%PP 18%PES 2%PU</p>  <p><b>Width</b> 140 + 4cm</p> <p><b>Weight</b> 764 gr/m<sup>2</sup> ± 5 % 1070 gr/lm ± 5 %</p> <p><b>Custom code</b> UE: 5903.20.90 USA: 5903.20.18.00</p> <p><b>Laboratory test number</b> IN-00261-2017</p>	<p><b>Seam slippage resistance (mm)</b> 2,00 EN ISO 13936/2:2004 3,00</p>  <p><b>Abrasion resistance (End point)</b> &gt;100.000 EN ISO 12947-2:1998</p>  <p><b>Pilling resistance</b> 5 EN ISO 12945/2:2000</p>  <p><b>Lightfastness to weather</b> ≥6 EN ISO 105-B04:1997 (1000 hours)</p>  <p><b>Colour fastness to rubbing</b> 4-5 EN ISO 105-X12:2002 4-5</p>  <p><b>Colour fastness to domestic and commercial laundering (30°)</b> 4-5 EN ISO 105-C06:1997/AC:2009</p>  <p><b>Water repellency (Hydrophobia)</b> &gt;2000mbar (20 mtrs) AATCC 79:2000</p>  <p><b>Resistance to putrefaction (Mould &amp; bacterium resist.)</b> YES EN 20811:1992 - AATCC 30:2004</p>	<p><b>Cleanability</b></p> <ul style="list-style-type: none"> <li>Spot-cleaning with soap and water</li> <li>No chemicals needed for cleaning</li> <li>Machine-washable</li> </ul>  <p><b>Washing conditions</b></p>  <p><b>Notes</b> Bleach cleanable 80% water 20% bleach. In case of mould growth, machine-wash with a mild laundry detergent and add 0,2 liter of household bleach to the first rinse cycle. Wash at 40°C during at least 30 minutes. Use gentle cycle with minimal centrifugation.</p> <p><b>Dimensional change domestic washing and drying (%)</b> -3,00% -1,00% EN ISO 3759:2008, EN ISO 6330:2000, EN ISO 5077:2008</p>  <p><b>Urine fastness</b> 4-5 EN ISO 105-E01:1996</p>  <p><b>Swimming pool chlorine fastness</b> 4-5 EN ISO 105-E03:1993</p>  <p><b>Sea water fastness</b> 4-5 EN ISO 105-E02:1996</p> 	<p>BS5852 Source 0 ✓ BS5852 Source 1 ✓ EN1021-Part 1:2006 ✓ EN1021-Part 2:2006 ✓ CAL TB 117:2013 ✓ NFPA 260:2013 ✓ BS 7176 Low Hazard UPON REQUEST ✓ UNI 9175 Clase 3IM UPON REQUEST ✓ IMO Anexo 1 Parte 8 ✓</p> <p><b>Notes</b> Recommendation: Distance overlock and stitch: 12 mm + 0,5 mm minimum Needle thickness: 110 Nm Thread: Polyester - Cotton 74 Tex (n°36) Stitch density: 4.0 stitches+0,1 stitches/cm</p> <p><b>Attention</b> When confectioning or washing the sofa cover with velcro please attach a protective cloth.</p>	<p><b>Environmental composition</b></p>  <p>18% = 6 bottles</p> <ul style="list-style-type: none"> <li>Recycled yarn 18%             <ul style="list-style-type: none"> <li>GRS Recycled PET bottles 18%</li> </ul> </li> <li>Standard yarn 82%             <ul style="list-style-type: none"> <li>Low-impact yarn (PP) 82%</li> </ul> </li> </ul> <p><b>Sustainability</b></p> <ul style="list-style-type: none"> <li>Oekotex certified</li> <li>REACH approved chemicals and dyes</li> <li>Biocide and PFCs free</li> <li>Zero-waste production</li> <li>Manufactured under ISO 9001 and ISO 14001 standards</li> <li>Made in Barcelona (EU)</li> </ul> 

Rev. nº: 8 - 19/08/2020

Results underline are obtained by Crevin's internal laboratory and must therefore be seen as indicative.