





















Characteristics 	Specifications 	Care 	Ignitability 	Environment 
<p><b>Total composition</b> 85%PES 15%CO</p>  <p><b>Width</b> 140 + 4cm</p> <p><b>Weight</b> 529 gr/m<sup>2</sup> ± 5 % 740 gr/lm ± 5 %</p> <p><b>Custom code</b> UE: 5801.36.00 USA: 5801.36.00.20</p> <p><b>Laboratory test number</b> IN-01202/2014-E-1 IN-00806/2015-E IN-01193/2017-1a</p>	<p><b>Seam slippage resistance (mm)</b> <span style="float:right">2,50</span> EN ISO 13936/2:2004 <span style="float:right">2,33</span></p>  <p><b>Abrasion resistance (End point)</b> <span style="float:right">80.000</span> EN ISO 12947-2:1998</p>  <p><b>Abrasion resistance (Full worn off)</b> <span style="float:right">30.000</span> EN ISO 12947-2:1998</p>  <p><b>Abrasion resistance (change of aspect: 3000 cycles)</b> <span style="float:right">4-5</span> EN ISO 12947/4:1998 and EN 14465:2003 (Annex A)</p>  <p><b>Pilling resistance</b> <span style="float:right">4-5</span> EN ISO 12945/2:2000</p>  <p><b>Lightfastness</b> <span style="float:right">5-6</span> EN ISO 105-B02:1998 &amp; 105 B02/A01:2002</p>  <p><b>Colour fastness to rubbing</b> <span style="float:right">4-5</span> EN ISO 105-X12:2002 <span style="float:right">4-5</span></p> 	<p><b>Soiling and cleanability</b> <span style="float:right">4</span> FORD FLTM BN 112-08:2005</p>  <ul style="list-style-type: none"> <li>Spot-cleaning with soap and water</li> <li>No chemicals needed for cleaning</li> <li>Machine-washable</li> </ul>  <p><b>Washing conditions</b></p>  <p><b>Dimensional change domestic washing and drying (%)</b> <span style="float:right">-2,00%</span> <span style="float:right">-3,00%</span> EN ISO 3759:2008, EN ISO 6330:2000, EN ISO 5077:2008</p> 	<p><b>BS5852 Source 0</b> <span style="float:right">✓</span></p> <p><b>BS5852 Source 1</b> <span style="float:right">UPON REQUEST</span></p> <p><b>EN1021-Part 1</b> <span style="float:right">✓</span></p> <p><b>EN1021-Part 2</b> <span style="float:right">UPON REQUEST</span></p> <p><b>CAL TB 117</b> <span style="float:right">✓</span></p> <p><b>NFPA 260</b> <span style="float:right">✓</span></p> <p><b>BS 7176 Low Hazard</b> <span style="float:right">UPON REQUEST</span></p> <p><b>UNI 9175 Clase 3IM</b> <span style="float:right">UPON REQUEST</span></p> <p><b>Attention</b> When confecting or washing a sofa cover with velcro, attach a protective strip to avoid damage to the fabric.</p>	<p><b>Environmental composition</b></p>  <p><b>Recycled yarn 21%</b></p> <ul style="list-style-type: none"> <li>GRS Recycled CO waste <span style="float:right">8%</span></li> <li>GRS Recycled PET bottles <span style="float:right">13%</span></li> </ul> <p><b>Standard yarn 79%</b></p> <ul style="list-style-type: none"> <li>PES yarn <span style="float:right">72%</span></li> <li>CO yarn <span style="float:right">7%</span></li> </ul> <p><b>Sustainability</b></p> <ul style="list-style-type: none"> <li>Oekotex certified</li> <li>REACH approved chemicals and dyes</li> <li>Biocide and PFCs free</li> <li>Zero-waste production</li> <li>Manufactured under ISO 9001 and ISO 14001 standards</li> <li>Made in Barcelona (EU)</li> </ul> 