























Characteristics 	Specifications 	Care 	Ignitability 	Environment 
<p><b>Total composition</b>  <b>47%PP 20%MA 15%CO 13%PES</b>  <b>5%PU</b></p>  <p><b>Width</b>  <b>140 + 4cm</b></p> <p><b>Weight</b>  <b>476 gr/m<sup>2</sup> ± 5 %</b>  <b>666 gr/lm ± 5 %</b></p> <p><b>Custom code</b>  <b>UE: 5903.20.90</b>  <b>USA: 5903.20.18.00</b></p> <p><b>Laboratory test number</b>                      IN-01025/2014                      IN-00357/2010                      IN-02081/2015</p>	<p><b>Seam slippage resistance (mm)</b> <b>1,90</b>                      EN ISO 13936/2:2004  </p> <p><b>Abrasion resistance (End point)</b> <b>60.000</b>                      EN ISO 12947-2:1998  </p> <p><b>Abrasion resistance (change of aspect: 3000 cycles)</b> <b>4-5</b>                      EN ISO 12947/4:1998 and EN 14465:2003 (Annex A)  </p> <p><b>Pilling resistance</b> <b>4-5</b>                      EN ISO 12945/2:2000  </p> <p><b>Lightfastness to weather</b> <b>&gt;6</b>                      EN ISO 105-B04:1997 (1000 hours)  </p> <p><b>Colour fastness to rubbing</b> <b>4-5</b>                      EN ISO 105-X12:2002                      DRY: 4-5                      WET: 4-5  </p> <p><b>Resistance to water penetration</b> <b>&gt;2000mbar</b>  </p> <p><b>Resistance to putrefaction (Mould &amp; bacterium resist.)</b> <b>Face fabric</b>  </p> <p><b>Swimming pool chlorine fastness</b> <b>4-5</b>                      EN ISO 105-E03:1993  </p>	<p><b>Soiling and cleanability</b> <b>4</b>                      FORD FLTM BN 112-08:2005  </p> <ul style="list-style-type: none"> <li>• Permanent protection against stains</li> <li>• Spot-cleaning with soap and water</li> <li>• No chemicals needed for cleaning</li> <li>• Machine-washable</li> </ul>  <p><b>Washing conditions</b>  </p> <p><b>Notes</b>                      Bleach cleanable 80% water 20% bleach. In case of mould growth, machine-wash with a mild laundry detergent and add 0,2 liter of household bleach to the first rinse cycle. Wash at 40° C during at least 30 minutes. Use gentle cycle with minimal centrifugation.</p> <p><b>Dimensional change domestic washing and drying (%)</b> <b>-2,00%</b>                      EN ISO 3759:2008, EN ISO 6330:2000, EN ISO 5077:2008                      WARP: -2,00%                      WEFT: -2,00%  </p> <p><b>Sea water fastness</b> <b>4-5</b>                      EN ISO 105-E02:1996  </p> <p><b>Urine fastness</b> <b>4-5</b>                      EN ISO 105-E03:1996  </p>	<p><b>BS5852 Source 0</b> ✓  <b>BS5852 Source 1</b> ✓  <b>EN1021-Part 1:2006</b> ✓  <b>EN1021-Part 2:2006</b> ✓  <b>CAL TB 117:2013</b> ✓  <b>NFPA 260:2013</b> ✓  <b>BS 7176 Low Hazard</b> ✓  <b>UNI 9175 Clase 3IM</b> ✓  <b>IMO Anexo 1 Parte 8</b> ✓</p> <p><b>Notes</b>                      STAIN REPELLENCE PROTECTION</p> <p><b>Attention</b>                      When confectioning or washing the sofa cover with velcro please attach a protective cloth.</p>	<p><b>Environmental composition</b></p>  <p><b>Recycled yarn 30%</b></p> <ul style="list-style-type: none"> <li>• GRS Recycled PET bottles <b>14%</b></li> <li>• GRS Recycled CO waste <b>16%</b></li> </ul> <p><b>Standard yarn 70%</b></p> <ul style="list-style-type: none"> <li>• Low-impact yarn (PP) <b>49%</b></li> <li>• MA yarn <b>21%</b></li> </ul> <p><b>Sustainability</b></p> <ul style="list-style-type: none"> <li>• Oekotex certified</li> <li>• REACH approved chemicals and dyes</li> <li>• Biocide and PFCs free</li> <li>• Zero-waste production</li> <li>• Manufactured under ISO 9001 and ISO 14001 standards</li> <li>• Made in Barcelona (EU)</li> </ul> 