






| Characteristics   | Specifications   | Care   | Ignitability   | Environment   |
|--|---|---|---|--|
| <p><b>Total composition</b><br/>100%PES FR</p>  <p><b>Width</b><br/>140 + 4cm</p> <p><b>Weight</b><br/>488 gr/m<sup>2</sup> ± 5 %<br/>707 gr/lm ± 5 %</p> <p><b>Custom code</b><br/>UE: 6005.38.00<br/>USA: 6005.38.00</p> <p><b>Laboratory test number</b><br/>IN-02209-2018-B-2</p> | <p><b>Seam slippage resistance (mm)</b> 1,70<br/>EN ISO 13936/2:2004 2,50</p>  <p><b>Abrasion resistance (End point)</b> 50.000<br/>EN ISO 12947-2:1998</p>  <p><b>Abrasion resistance (change of aspect: 3000 cycles)</b> 3-4<br/>EN ISO 12947/4:1998 and EN 14465:2003 (Annex A)</p>  <p><b>Pilling resistance</b> 4-5<br/>EN ISO 12945/2:2000</p>  <p><b>Lightfastness</b> 6-7<br/>EN ISO 105-B02:1998 &amp; 105 B02/A01:2002</p>  <p><b>Colour fastness to rubbing</b> 5<br/>EN ISO 105-X12:2002 4-5</p>  | <p><b>Soiling and cleanability</b> 4-5<br/>FORD FLTM BN 112-08:2005</p>  <p><b>Washing conditions</b></p>  <p><b>Dimensional change domestic washing and drying (%)</b> -3,00%<br/>-1,50%<br/>EN ISO 3759:2008, EN ISO 6330:2000, EN ISO 5077:2008</p>  | <p>BS5852 Source 0 ✓<br/>BS5852 Source 1 ✓<br/>EN1021-Part 1 ✓<br/>EN1021-Part 2 ✓<br/>CAL TB 117 ✓<br/>NFPA 260 ✓<br/>BS 7176 Low Hazard ✓<br/>UNI 9175 Clase 1IM ✓<br/>BS5852 0 ✓<br/>EN 1021 1 ✓<br/>IMO Annex 1 Part 8 ✓<br/>NF D 60 013 ✓<br/>DIN 4102 B2 ✓</p> <p>Acoustic certificate:<br/>EN ISO 354 ✓</p> <p><b>Notes</b><br/>Slight colour variations may occur from batch to batch.</p> <p><b>Attention</b><br/>When confectioning or washing a sofa cover with velcro, attach a protective strip to avoid damage to the fabric.</p> | <p><b>Sustainability</b></p> <ul style="list-style-type: none"> <li>• Oekotex certified</li> <li>• REACH approved chemicals and dyes</li> <li>• Biocide and PFCs free</li> <li>• Zero-waste production</li> <li>• Manufactured under ISO 9001 and ISO 14001 standards</li> <li>• Made in Barcelona (EU)</li> </ul>  |