























| Characteristics  | Specifications  | Care  | Ignitability  | Environment  |
|--|---|--|---|--|
| <p>Total composition 74%PP 26%PES</p>  <p>Width 140 + 4cm</p> <p>Weight 500 gr/m² ± 5 % 700 gr/lm ± 5 %</p> <p>Custom code UE: 5407.73.00 USA: 5407.73.20.60</p> <p>Laboratory test number IN-01101-2019-B 2019AN1765</p> | <p>Seam slippage resistance (mm) 3,60 EN ISO 13936/2:2004 WARP 2,30</p>  <p>Abrasion resistance (End point) 40.000 EN ISO 12947-2:1998</p>  <p>Abrasion resistance (change of aspect: 3000 cycles) 4-5 EN ISO 12947/4:1998 and EN 14465:2003 (Annex A)</p>  <p>Pilling resistance 4-5 EN ISO 12945/2:2000</p>  <p>Lightfastness to weather >6 EN ISO 105-B04:1997 (1000 hours)</p>  <p>Colour fastness to rubbing 4-5 EN ISO 105-X12:2002 4-5 DRY 4-5 WET</p>  <p>Colour fastness to domestic and commercial laundering (30°) 4-5 EN ISO 105-C06:1997/AC:2009</p>  <p>Resistance to putrefaction (Mould & bacterium resist.) Face fabric</p> <p>Swimming pool chlorine fastness 4-5 EN ISO 105-E03:1993</p>  | <p>Soiling and cleanability 4-5 FORD FLTM BN 112-08:2005</p>  <ul style="list-style-type: none"> Permanent protection against stains Spot-cleaning with soap and water No chemicals needed for cleaning Machine-washable  <p>Washing conditions</p>  <p>Notes Bleach cleanable 80% water 20% bleach. In case of mould growth, machine-wash with a mild laundry detergent and add 0,2 liter of household bleach to the first rinse cycle. Wash at 40° C during at least 30 minutes. Use gentle cycle with minimal centrifugation.</p> <p>Dimensional change domestic washing and drying (%) -2,60% -0,60% EN ISO 3759:2008, EN ISO 6330:2000, EN ISO 5077:2008</p>  <p>Sea water fastness 4-5 EN ISO 105-E02:1996</p>  <p>Urine fastness 4-5 EN ISO 105-E03:1996</p>  | <p>BS5852 Source 0 ✓ BS5852 Source 1 UPON REQUEST ✓ EN1021-Part 1 UPON REQUEST ✓ EN1021-Part 2 ✓ CAL TB 117 ✓ NFPA 260 ✓</p> <p>Attention When confectioning or washing the sofa cover with velcro please attach a protective cloth.</p> | <p>Environmental composition</p>  <p>• Recycled yarn 26% • GRS Recycled PET bottles 26%</p> <p>• Standard yarn 74% • Low-impact yarn (PP) 74%</p> <p>Sustainability</p> <ul style="list-style-type: none"> Oekotex certified REACH approved chemicals and dyes Biocide and PFCs free Zero-waste production Manufactured under ISO 9001 and ISO 14001 standards Made in Barcelona (EU)  |