




















Characteristics 	Specifications 	Care 	Ignitability 	Environment 
<p><b>Total composition</b>                      49%PP 21%MA 16%CO 14%PES</p>  <p><b>Width</b>                      140 + 4cm</p> <p><b>Weight</b>                      450 gr/m<sup>2</sup> ± 5 %                      630 gr/lm ± 5 %</p> <p><b>Custom code</b>                      UE: 5407.83.00                      USA: 5407.83.00.90</p> <p><b>Laboratory test number</b>                      Docs. 11835, 11836, 11850</p>	<p><b>Seam slippage resistance (mm)</b> <span style="float:right">1,60</span>                      EN ISO 13936/2:2004 <span style="float:right">1,00</span></p>  <p><b>Abrasion resistance (End point)</b> <span style="float:right">66.000</span>                      EN ISO 12947-2:1998</p>  <p><b>Abrasion resistance (change of aspect: 3000 cycles)</b> <span style="float:right">4-5</span>                      EN ISO 12947/4:1998 and EN 14465:2003 (Annex A)</p>  <p><b>Pilling resistance</b> <span style="float:right">4-5</span>                      EN ISO 12945/2:2000</p>  <p><b>Lightfastness</b> <span style="float:right">≥6</span>                      EN ISO 105-B02:1998 &amp; 105 B02/A01:2002</p>  <p><b>Colour fastness to rubbing</b> <span style="float:right">4-5</span>                      EN ISO 105-X12:2002 <span style="float:right">4-5</span></p> 	<p><b>Soiling and cleanability</b> <span style="float:right">4-5</span>                      FORD FLTM BN 112-08:2005</p>  <ul style="list-style-type: none"> <li>Spot-cleaning with soap and water</li> <li>No chemicals needed for cleaning</li> <li>Machine-washable</li> </ul>  <p><b>Washing conditions</b></p>  <p><b>Notes</b>                      Bleach cleanable 80% water 20% bleach.</p> <p><b>Dimensional change domestic washing and drying (%)</b> <span style="float:right">-1,00%</span>  <span style="float:right">-1,00%</span>                      EN ISO 3759:2008, EN ISO 6330:2000, EN ISO 5077:2008</p>  <p><b>Attention</b>                      When confecting or washing the sofa cover with velcro please attach a protective cloth.</p>	<p>BS5852 Source 0 ✓                      BS5852 Source 1 ✓                      EN1021-Part 1:2006 ✓                      EN1021-Part 2:2006 ✓                      CAL TB 117:2013 ✓                      NFPA 260:2013 ✓                      BS 7176 Low Hazard ✓                      UNI 9175 Clase 3IM ✓                      IMO Anexo 1 Parte 8 ✓</p>	<p><b>Environmental composition</b></p>  <p><b>Recycled yarn 30%</b></p> <ul style="list-style-type: none"> <li>GRS Recycled PET bottles <span style="float:right">14%</span></li> <li>GRS Recycled CO waste <span style="float:right">16%</span></li> </ul> <p><b>Standard yarn 70%</b></p> <ul style="list-style-type: none"> <li>Low-impact yarn (PP) <span style="float:right">49%</span></li> <li>MA yarn <span style="float:right">21%</span></li> </ul> <p><b>Sustainability</b></p> <ul style="list-style-type: none"> <li>Oekotex certified</li> <li>REACH approved chemicals and dyes</li> <li>Biocide and PFCs free</li> <li>Zero-waste production</li> <li>Manufactured under ISO 9001 and ISO 14001 standards</li> <li>Made in Barcelona (EU)</li> </ul> 