






Characteristics	Specifications	Care	Ignitability	Environment
Total composition 42%PP 42%PES 16%CO  Width 140 + 4cm Weight 615 gr/m² ± 5 % 861 gr/lm ± 5 % Custom code UE: 5801.36.00 USA: 5801.36.00.20 Laboratory test number IN-00923/2014	Seam slippage resistance (mm) <u>1.00</u> EN ISO 13936/2:2004 <u>0.50</u>  Abrasion resistance (End point) <u>85.000</u> EN ISO 12947-2:1998  Abrasion resistance (change of aspect: 3000 cycles) <u>4-5</u> EN ISO 12947/4:1998 and EN 14465:2003 (Annex A)  Pilling resistance <u>4-5</u> EN ISO 12945/2:2000  Lightfastness <u>5-6</u> EN ISO 105-B02:1998 & 105 B02/A01:2002 	Soiling and cleanability <u>4</u> FORD FLTM BN 112-08:2005  - Spot-cleaning with soap and water - No chemicals needed for cleaning - Machine-washable  Washing conditions  Dimensional change domestic washing and drying (%) <u>-3.00%</u> <u>-2.00%</u> EN ISO 3759:2008, EN ISO 6330:2000, EN ISO 5077:2008 	BS5852 Source 0 ✓ BS5852 Source 1 UPON REQUEST ✓ EN1021-Part 1 UPON REQUEST ✓ EN1021-Part 2 UPON REQUEST ✓ CAL TB 117 ✓ NFPA 260 ✓ BS 7176 Low Hazard UPON REQUEST UNI 9175 Clase 3IM UPON REQUEST	Environmental composition  • Recycled yarn 21% - GRS Recycled PET bottles 15% - GRS Recycled CO waste 3% - Circular yarn from own waste 3% • Standard yarn 79% - Low-impact yarn (PP) 42% - PES yarn 27% - CO yarn 10% Sustainability - Oekotex certified - REACH approved chemicals and dyes - Biocide and PFCs free - Zero-waste production - Manufactured under ISO 9001 and ISO 14001 standards - Made in Barcelona (EU)
			Notes Recommendation: Distance overlock and stitch: 12 mm + 0,5 mm minimum Needle thickness: 110 Nm Thread: Polyester - Cotton 74 Tex (n°36) Stitch density: 4.0 stitches+0,1 stitches/cm Attention when confectioning or washing the sofa cover with velcro please attach a protective cloth.	