









Characteristics 	Specifications 	Care 	Ignitability 	Environment 
Total composition 76%PP 17%PES 7%CO  Width 140 + 4cm Weight 568 gr/m² ± 5 % 795 gr/lm ± 5 % Custom code UE: 5407.83.00 USA: 5407.83.00.90 Laboratory test number IN-00807-2018-B 2020AN1320 EN ISO 20743	Seam slippage resistance (mm) 1,90 EN ISO 13936/2:2004 1,70  Abrasion resistance (End point) 35.000 EN ISO 12947-2:1998  Abrasion resistance (change of aspect: 3000 cycles) 3-4 EN ISO 12947/4:1998 and EN 14465:2003 (Annex A)  Pilling resistance 4-5 EN ISO 12945/2:2000  Lightfastness ≥6 EN ISO 105-B02:1998 & 105 B02/A01:2002  Colour fastness to rubbing 4-5 EN ISO 105-X12:2002 4-5 	Soiling and cleanability 4-5 FORD FLTM BN 112-08:2005  - Spot-cleaning with soap and water - No chemicals needed for cleaning - Machine-washable  Washing conditions  Dimensional change domestic washing and drying (%) -3,00% -1,00% EN ISO 3759:2008, EN ISO 6330:2000, EN ISO 5077:2008  Antibacterial activity EN ISO 20743:2013 Strong antibacterial property >3 	BS5852 Source 0 ✓ BS5852 Source 1 UPON REQUEST ✓ EN1021-Part 1 UPON REQUEST ✓ EN1021-Part 2 UPON REQUEST ✓ CAL TB 117 ✓ NFPA 260 ✓ BS 7176 Low Hazard UPON REQUEST UNI 9175 Clase 3IM UPON REQUEST	Environmental composition  • Recycled yarn 24% - Circular yarn from own waste 4% - GRS Recycled PET bottles 17% - GRS Recycled CO waste 3% • Standard yarn 76% - Low-impact yarn (PP) 76% Sustainability - Oekotex certified - REACH approved chemicals and dyes - PFCs free - Zero-waste production - Manufactured under ISO 9001 and ISO 14001 standards - Made in Barcelona (EU)