





















Characteristics 	Specifications 	Care 	Ignitability 	Environment 
<p>Total composition 60%PP 40%PES</p>  <p>Width 140 + 4cm</p> <p>Weight 371 gr/m² ± 5 % 520 gr/lm ± 5 %</p> <p>Custom code UE: 5407.73.00 USA: 5407.73.20.60</p> <p>Laboratory test number IN-01025/2014 IN-00357/2010</p>	<p>Seam slippage resistance (mm) <u>1,90</u> EN ISO 13936/2:2004 <u>2,20</u></p>  <p>Abrasion resistance (End point) <u>60.000</u> EN ISO 12947-2:1998</p>  <p>Abrasion resistance (change of aspect: 3000 cycles) <u>4-5</u> EN ISO 12947/4:1998 and EN 14465:2003 (Annex A)</p>  <p>Pilling resistance <u>4-5</u> EN ISO 12945/2:2000</p>  <p>Lightfastness to weather <u>>6</u> EN ISO 105-B04:1997 (1000 hours)</p>  <p>Colour fastness to rubbing <u>4-5</u> EN ISO 105-X12:2002 <u>4-5</u></p>  <p>Resistance to putrefaction (Mould & bacterium resist.) <u>Upper fabric</u></p> <p>Swimming pool chlorine fastness <u>4-5</u> EN ISO 105-E03:1993</p> 	<p>Soiling and cleanability <u>4</u> FORD FLTM BN 112-08:2005</p>  <ul style="list-style-type: none"> Permanent protection against stains Spot-cleaning with soap and water No chemicals needed for cleaning Machine-washable  <p>Washing conditions</p>  <p>Notes Bleach cleanable 80% water 20% bleach. In case of mould growth, machine-wash with a mild laundry detergent and add 0,2 liter of household bleach to the first rinse cycle. Wash at 40 °C during at least 30 minutes. Use gentle cycle with minimal centrifugation.</p> <p>Dimensional change domestic washing and drying (%) <u>-2,00%</u> <u>-2,00%</u> EN ISO 3759:2008, EN ISO 6330:2000, EN ISO 5077:2008</p>  <p>Sea water fastness <u>4-5</u> EN ISO 105-E02:1996</p>  <p>Urine fastness <u>4-5</u> EN ISO 105-E03:1996</p> 	<p>BS5852 Source 0 ✓</p> <p>EN1021-Part 1:2006 ✓</p> <p>CAL TB 117:2013 ✓</p> <p>NFPA 260:2013 ✓</p> <p>BS 7176 Low Hazard UPON REQUEST</p> <p>UNI 9175 Clase 3IM UPON REQUEST</p> <p>Notes STAIN REPELLENCE PROTECTION</p> <p>Attention When confectioning or washing the sofa cover with velcro please attach a protective cloth.</p>	<p>Environmental composition</p>  <ul style="list-style-type: none"> Recycled yarn 40% <ul style="list-style-type: none"> GRS Recycled PET bottles 40% Standard yarn 60% <ul style="list-style-type: none"> Low-impact yarn (PP) 60% <p>Sustainability</p> <ul style="list-style-type: none"> Oekotex certified REACH approved chemicals and dyes Biocide and PFCs free Zero-waste production Manufactured under ISO 9001 and ISO 14001 standards Made in Barcelona (EU) 