










# crevin

## Vita (Imp)

outdoor • bleach cleanable • stain resistant • washable

Characteristics 	Specifications 	Care 	Ignitability 	Environment 
<p><b>Total composition</b> 57%PP 38%PES 5%PU</p>  <p><b>Width</b> 140 + 4cm</p> <p><b>Weight</b> 390 gr/m<sup>2</sup> ± 5 % 546 gr/lm ± 5 %</p> <p><b>Custom code</b> UE: 5903.20.90 USA: 5903.20.18.00</p> <p><b>Laboratory test number</b> IN-01025/2014 IN-00357/2010</p>	<p><b>Seam slippage resistance (mm)</b> <u>1,90</u> EN ISO 13936/2:2004 <u>2,20</u> WARP WEFT</p> <p><b>Abrasion resistance (End point)</b> <u>60.000</u> EN ISO 12947-2:1998</p> <p><b>Abrasion resistance (change of aspect: 3000 cycles)</b> <u>4-5</u> EN ISO 12947/4:1998 and EN 14465:2003 (Annex A)</p> <p><b>Pilling resistance</b> <u>4-5</u> EN ISO 12945/2:2000</p> <p><b>Lightfastness to weather</b> <u>&gt;6</u> EN ISO 105-B04:1997 (1000 hours)</p> <p><b>Colour fastness to rubbing</b> <u>4-5</u> EN ISO 105-X12:2002 <u>4-5</u> DRY WET</p> <p><b>Resistance to water penetration</b> <u>&gt;2000mbar</u></p> <p><b>Resistance to putrefaction (Mould &amp; bacterium resist.)</b> <u>Upper fabric</u></p> <p><b>Swimming pool chlorine fastness</b> <u>4-5</u> EN ISO 105-E03:1993</p>	<p><b>Soiling and cleanability</b> <u>4</u> FORD FLTM BN 112-08:2005</p> <ul style="list-style-type: none"> <li>Permanent protection against stains</li> <li>Spot-cleaning with soap and water</li> <li>No chemicals needed for cleaning</li> <li>Machine-washable</li> </ul>  <p><b>Washing conditions</b></p>  <p><b>Notes</b> Bleach cleanable 80% water 20% bleach. In case of mould growth, machine-wash with a mild laundry detergent and add 0,2 liter of household bleach to the first rinse cycle. Wash at 40 °C during at least 30 minutes. Use gentle cycle with minimal centrifugation.</p> <p><b>Dimensional change domestic washing and drying (%)</b> <u>-2,00%</u> EN ISO 3759:2008, EN ISO 6330:2000, EN ISO 5077:2008 WARP WEFT</p> <p><b>Sea water fastness</b> <u>4-5</u> EN ISO 105-E02:1996</p> <p><b>Urine fastness</b> <u>4-5</u> EN ISO 105-E03:1996</p>	<p>BS5852 Source 0 ✓ EN1021-Part 1:2006 ✓ CAL TB 117:2013 ✓ NFPA 260:2013 ✓ BS 7176 Low Hazard UPON REQUEST UNI 9175 Clase 3IM UPON REQUEST</p> <p><b>Notes</b> STAIN REPELLENCE PROTECTION</p> <p><b>Attention</b> When confectioning or washing the sofa cover with velcro please attach a protective cloth.</p>	<p><b>Environmental composition</b></p>  <p>• Recycled yarn <b>40%</b> • GRS Recycled PET bottles <b>40%</b> • Standard yarn <b>60%</b> • Low-impact yarn (PP) <b>60%</b></p> <p><b>Sustainability</b></p> <ul style="list-style-type: none"> <li>Oekotex certified</li> <li>REACH approved chemicals and dyes</li> <li>Biocide and PFCs free</li> <li>Zero-waste production</li> <li>Manufactured under ISO 9001 and ISO 14001 standards</li> <li>Made in Barcelona (EU)</li> </ul> 