























Characteristics 	Specifications 	Care 	Ignitability 	Environment 
<p>Total composition 47%PP 20%MA 15%CO 13%PES 5%PU</p>  <p>Width 140 + 4cm</p> <p>Weight 476 gr/m² ± 5 % 666 gr/lm ± 5 %</p> <p>Custom code UE: 5903.20.90 USA: 5903.20.18.00</p> <p>Laboratory test number IN-01025/2014 IN-00357/2010 IN-02081/2015</p>	<p>Seam slippage resistance (mm) 1,90 <small>EN ISO 13936/2:2004</small> </p> <p>Abrasion resistance (End point) 60.000 <small>EN ISO 12947-2:1998</small> </p> <p>Abrasion resistance (change of aspect: 3000 cycles) 4-5 <small>EN ISO 12947/4:1998 and EN 14465:2003 (Annex A)</small> </p> <p>Pilling resistance 4-5 <small>EN ISO 12945/2:2000</small> </p> <p>Lightfastness to weather >6 <small>EN ISO 105-B04:1997 (1000 hours)</small> </p> <p>Colour fastness to rubbing 4-5 <small>EN ISO 105-X12:2002</small> </p> <p>Resistance to water penetration >2000mbar </p> <p>Resistance to putrefaction (Mould & bacterium resist.) Face fabric </p> <p>Swimming pool chlorine fastness 4-5 <small>EN ISO 105-E03:1993</small> </p>	<p>Soiling and cleanability 4 <small>FORD FLTM BN 112-08:2005</small> </p> <ul style="list-style-type: none"> • Permanent protection against stains • Spot-cleaning with soap and water • No chemicals needed for cleaning • Machine-washable  <p>Washing conditions </p> <p>Notes Bleach cleanable 80% water 20% bleach. In case of mould growth, machine-wash with a mild laundry detergent and add 0,2 liter of household bleach to the first rinse cycle. Wash at 40° C during at least 30 minutes. Use gentle cycle with minimal centrifugation.</p> <p>Dimensional change domestic washing and drying (%) -2,00% <small>EN ISO 3759:2008, EN ISO 6330:2000, EN ISO 5077:2008</small> </p> <p>Sea water fastness 4-5 <small>EN ISO 105-E02:1996</small> </p> <p>Urine fastness 4-5 <small>EN ISO 105-E01:1996</small> </p>	<p>BS5852 Source 0 ✓ BS5852 Source 1 ✓ EN1021-Part 1:2006 ✓ EN1021-Part 2:2006 ✓ CAL TB 117:2013 ✓ NFPA 260:2013 ✓ BS 7176 Low Hazard ✓ UNI 9175 Clase 3IM ✓ IMO Anexo 1 Parte 8 ✓</p> <p>Notes STAIN REPELLENCE PROTECTION</p> <p>Attention When confectioning or washing the sofa cover with velcro please attach a protective cloth.</p>	<p>Environmental composition</p>  <ul style="list-style-type: none"> • Recycled yarn 30% <ul style="list-style-type: none"> • GRS Recycled PET bottles 14% • GRS Recycled CO waste 16% • Standard yarn 70% <ul style="list-style-type: none"> • Low-impact yarn (PP) 49% • MA yarn 21% <p>Sustainability</p> <ul style="list-style-type: none"> • Oekotex certified • REACH approved chemicals and dyes • Biocide and PFCs free • Zero-waste production • Manufactured under ISO 9001 and ISO 14001 standards • Made in Barcelona (EU) 