





















Characteristics 	Specifications 	Care 	Ignitability 	Environment 
<p><b>Total composition</b> 84%PP 16%PES</p>  <p><b>Width</b> 140 + 4cm</p> <p><b>Weight</b> 530 gr/m<sup>2</sup> ± 5 % 742 gr/lm ± 5 %</p> <p><b>Custom code</b> UE: 5407.73.00 USA: 5407.73.20.60</p> <p><b>Laboratory test number</b> 2019AN1636</p>	<p><b>Seam slippage resistance (mm)</b> <span style="float:right">2,00</span> EN ISO 13936/2:2004 <span style="float:right">2,60</span></p>  <p><b>Abrasion resistance (End point)</b> <span style="float:right">30.000</span> EN ISO 12947-2:1998</p>  <p><b>Pilling resistance</b> <span style="float:right">4-5</span> EN ISO 12945/2:2000</p>  <p><b>Lightfastness to weather</b> <span style="float:right">&gt;6</span> EN ISO 105-B04:1997 (1000 hours)</p>  <p><b>Colour fastness to rubbing</b> <span style="float:right">4-5</span> EN ISO 105-X12:2002 <span style="float:right">4-5</span></p>  <p><b>Colour fastness to domestic and commercial laundering (30°)</b> <span style="float:right">4-5</span> EN ISO 105-C06:1997/AC:2009</p>  <p><b>Resistance to putrefaction (Mould &amp; bacterium resist.)</b> <span style="float:right">Face fabric</span></p> <p><b>Swimming pool chlorine fastness</b> <span style="float:right">4-5</span> EN ISO 105-E03:1993</p> 	<p><b>Soiling and cleanability</b> <span style="float:right">4-5</span> FORD FLTM BN 112-08:2005</p>  <ul style="list-style-type: none"> <li>Permanent protection against stains</li> <li>Spot-cleaning with soap and water</li> <li>No chemicals needed for cleaning</li> <li>Machine-washable</li> </ul>  <p><b>Washing conditions</b></p>  <p><b>Notes</b> Bleach cleanable 80% water 20% bleach. In case of mould growth, machine-wash with a mild laundry detergent and add 0,2 liter of household bleach to the first rinse cycle. Wash at 40° C during at least 30 minutes. Use gentle cycle with minimal centrifugation.</p> <p><b>Dimensional change domestic washing and drying (%)</b> <span style="float:right">-2,00%</span> <span style="float:right">-0,80%</span> EN ISO 3759:2008, EN ISO 6330:2000, EN ISO 5077:2008</p>  <p><b>Sea water fastness</b> <span style="float:right">4-5</span> EN ISO 105-E02:1996</p>  <p><b>Urine fastness</b> <span style="float:right">4-5</span> EN ISO 105-E01:1996</p> 	<p>BS5852 Source 0 <span style="float:right">✓</span> EN1021-Part 1:2006 <span style="float:right">✓</span> CAL TB 117:2013 <span style="float:right">✓</span> NFPA 260:2013 <span style="float:right">✓</span></p> <p><b>Notes</b> STAIN REPELLENCE PROTECTION</p> <p><b>Attention</b> When confectioning or washing the sofa cover with velcro please attach a protective cloth.</p>	<p><b>Environmental composition</b></p>  <p>• Recycled yarn <b>16%</b>              • GRS Recycled PET bottles <b>16%</b>              • Standard yarn <b>84%</b>              • Low-impact yarn (PP) <b>84%</b></p> <p><b>Sustainability</b></p> <ul style="list-style-type: none"> <li>Oekotex certified</li> <li>REACH approved chemicals and dyes</li> <li>Biocide and PFCs free</li> <li>Zero-waste production</li> <li>Manufactured under ISO 9001 and ISO 14001 standards</li> <li>Made in Barcelona (EU)</li> </ul> 