### Bora Bora

## crevin

# outdoor • bleach cleanable • fire resistant General Information Specifications Seam slippage resistance (mm) Warp: 2,00 Warp: 2,00 Weft: 3,00 EN ISO 13936/2:2004 Abrasion resistance (End point)



Composition 82%PP 18%PES REC

**Width** 140 + 4cm

Weight 750 gr/m2 ± 5 % 1050 gr/lm ± 5 %

**Custom code** UE: 5407.73.00 USA: 5407.73.20.60

Laboratory test number IN-00261-2017 WYS85789 AN0584 Abrasion resistance (End point) >100.000 EN ISO 12947-2:1998

Pilling resistance 5 EN ISO 12945/2:2000

Lightfastness to weather ≥6 EN ISO 105-B04:1997 (1000 hours)

**Colour fastness to rubbing** Wet: <u>4-5</u> Dry: <u>4-5</u> EN ISO 105-X12:2002

Colour fastness to domestic and comercial laundering (30°) <u>4-5</u> EN ISO 105-C06:1997/AC:2009

Water repellency (Hydrophobia) >2000mbar (20 mtrs) AATCC 79:2000

**Swimming pool chlorine fastness** <u>4-5</u> EN ISO 105-E03:1993

Sea water fastness 4-5 EN ISO 105-E02:1996

**Urine fastness** <u>4-5</u> EN ISO 105-E01:1996

#### Care

Washing conditions



Dimensional change domestic washing and drying (%) Warp: <u>-3</u> Weft: <u>-1</u> EN ISO 3759:2008, EN ISO 6330:2000 and EN ISO 5077:2008

Bleach cleanable 80% water 20% bleach. In case of mould growth, machine-wash with a mild laundry detergent and add 0,2 liter of household bleach to the first rinse cycle. Wash at 40°C during at least 30 minutes. Use gentle cycle with minimal centrifugation.

When confectioning or washing the sofa cover with velcro please attach a protective cloth.

Notes: Recomendation: Distance overlock and stitch: 12 mm + 0,5 mm minimum Needle thickness: 110 Nm Thread: Polyester - Cotton 74 Tex (n°36) Stitch density: 4.0 stitches+0,1 stitches/cm

#### Ignitability

BS5852 Source 0 EN1021-Part 1:2006 CAL TB 117:2013 NFPA 260:2013 BS5852 Source 1 EN1021-Part 2:2006 IMO Anexo 1 Parte 8

Upon Request: BS 7176 Low Hazard UNI 9175 Clase 3IM

#### Environmental considerations

## 18% GRS recycled PET bottles 82% Low impact yarn (PP)

in Terrassa (Barcelona)

#### Life cycle analysis

Cradle to gate assessment. From raw material extraction to finished fabric: resources, yarn production and dyeing, fabric weaving and finishing, waste recycling.

Carbon footprint



#### Water consumption



Certificates



#### UNIVERSITAT POLITÈCNICA DE CATALUNYA BARCELONATECH

Escola Superior d'Enginyeries Industrial, Aeroespacial i Audiovisual de Terrassa

Study realized in collaboration with UPC

Methodology: Life Cycle Analysis. ISO 14040 standard.

Database: Own data, Ecoinvent 3.6 database and published data.

Functional unit: 1 linear meters, 140 cm width.

Calculation methodology: ReCiPe Midpoint (H) 2016 v1.0 ReCiPe Endpoint (H) 2016 v1.04 IPCC 2013 GWP 100a v1.03



Rev. nº: 9 - 24/08/2022 \*Results have been obtained by Crevin's internal laboratory and must therefore be seen as indicative.