Brisa

crevin

outdoor • easy stain release • bleach cleanable General Information **Specifications** Care Washing conditions Seam slippage resistance (mm) Warp: 2,0 $\boxtimes \triangle \boxtimes \not \supseteq \bigcirc w$ Weft: 1,80 EN ISO 13936/2:2004 Soiling and cleanability 4 FORD FLTM BN 112-08:2005 Abrasion resistance (End point) 71.000 EN ISO 12947-2:1998 **Dimensional change domestic** Abrasion resistance washing and drying (%) (change of aspect: 3000 cycles) Warp: -3 3-4 EN ISO 12947/4:1998 Weft: <u>-2</u> and EN 14465:2003 (Annex A) **Pilling resistance** Bleach cleanable 80% water 20% bleach. Pilling 4-5 / Fuzzing 3-4 In case of mould growth, machine-wash with a mild laundry detergent and add 0,2 liter of household bleach to the first rinse cycle. Wash at 40° C during at least 30 minutes. Use gentle cycle with minimal centrifugation. Lightfastness to weather >6 EN ISO 105-B04:1997 (1000 hours) When confectioning or washing the sofa cover with velcro please attach a protective cloth. Composition 74%PP 26%PES REC Colour fastness to rubbing Wet: 4-5 Dry: 4-5 Width EN ISO 105-X12:2002 140 + 4cm Swimming pool chlorine fastness Weight 4-5 EN ISO 105-E03:1993 $443 \, \text{gr/m2} \pm 5 \, \%$ $620 \text{ gr/lm} \pm 5\%$ Ignitability Sea water fastness 4-5 EN ISO 105-E02:1996 Custom code BS5852 Source 0 Upon Request: UE: 5407.73.00 **Urine fastness** EN1021-Part 1:2006 USA: 5407.73.20.60 4-5 EN ISO 105-E01:1996 EN1021-Part 2:2006 CAL TB 117:2013 NFPA 260:2013 BS 7176 Low Hazard Laboratory test number UNI 9175 Clase 3IM IN-01417-2023-1 218352-4 IMO Anexo 1 Parte 8 **Environmental considerations** Life cycle analysis UNIVERSITAT POLITÈCNICA DE CATALUNYA BARCELONATECH Cradle to gate assessment. From raw Escola Superior d'Enginyeries Industrial, Aeroespacial i Audiovisual de Terrassa material extraction to finished fabric: resources, yarn production and dyeing, fabric weaving and finishing, waste recycling. Study realized in collaboration with UPC Methodology: ecycled yarı Life Cycle Analysis. ISO 14040 standard. **Carbon footprint** Database[.] Own data, Ecoinvent 3.6 database and In process $kg CO_2 eq/m$ published data.

Functional unit: 1 linear meters, 140 cm width.

> Calculation methodology: ReCiPe Midpoint (H) 2016 v1.0 ReCiPe Endpoint (H) 2016 v1.04 IPCC 2013 GWP 100a v1.03



in Terrassa (Barcelona)

Water consumption

Certificates

In process liters/m

Rev. nº: 3 - 24/08/2023 *Results have been obtained by Crevin's internal laboratory and must therefore be seen as indicative.

26% GRS recycled PET bottles 74% Low impact varn (PP)

Designed and Crafted