Trena

crevin

stretch • easy stain release

General Information

Composition
88%PES 12%PET REC

Width
140 + 4cm

Weight
811 gr/m2 ± 5 %
1136 gr/lm ± 5 %

Custom code
UE: 6005.38.00
USA: 6005.38.00

Laboratory test number
IN-00060-2025-1 / 2025 AN 0959 / 601010-01

Specifications

Seam slippage resistance (mm)
Warp: 2
Weft: 1,1
EN ISO 13936/2:2004

Abrasion resistance (End point)
EN ISO 12947-2:2016
Tested for decorative use: 25.000

Abrasion resistance (change of aspect: 3000 cycles)
4 EN ISO 12947/4:1998 and EN 14465:2003 (Annex A)

Pilling resistance
4 EN ISO 12945/2:2020

Bursting strenght
878,15 Level A
EN ISO 13938-2:2019

Lightfastness
5-6 EN ISO 105-B02:1998 and 105 B02/A01:2002

Colour fastness to rubbing
Dry: 4-5
Wet: 4-5
EN ISO 105-X12:2002

Care

Washing conditions



Soiling and cleanability
4 FORD FLTM BN 112-08:2005

Dimensional change domestic washing and drying (%)
Warp: -3%
Weft: -2%
EN ISO 3759:2008, EN ISO 6330:2000 and EN ISO 5077:2008

When confectioning or washing the sofa cover with velcro please attach a protective cloth.

Ignitability

BS5852 Source 0
EN1021-Part 1:2006
CAL TB 117:2013
NFPA 260:2013

Environmental considerations



12% GRS recycled PET bottles
88% PES

Life Cycle Scope
Cradle to grave assessment. From raw material extraction to fabric recycling: resources, yarn production and dyeing, weaving and fabric finishing, waste recycling, daily use, and end-of-life.

Carbon footprint
8,91 kg CO_2 eq/m

Water consumption
219,72 liters/m

UNIVERSITAT POLITÈCNICA DE CATALUNYA
BARCELONATECH
Escola Superior d'Enginyeries Industrial, Aeroespacial i Audiovisual de Terrassa

Study realized in collaboration with UPC

Methodology:
Life Cycle Analysis. ISO 14040 standard.

Database:
Own data, Ecoinvent 3.6 database and published data.

Functional unit:
1 linear meters, 140 cm width.

Calculation methodology:
ReCiPe Midpoint (H) 2016 v1.0
ReCiPe Endpoint (H) 2016 v1.04
IPCC 2013 GWP 100a v1.03

Usage scenario:
1 home wash per year
1 vacuum per month
For 15 years

End-of-life scenario:
75% Landfill
20% Incineration
5% Recycling

Designed and Crafted in Terrassa (Barcelona)

Certificates

AENOR ZERO WASTE · OEKO TEX STANDARD 100 · ISO 9001 · ISO 14001 · PFAS FREE · REACH

 *Results that are underlined have been obtained by Crevin's internal laboratory and must therefore be seen as indicative.