Corda (Imp)

crevin

outdoor • waterproof • fire resistant • easy stain release • bleach cleanable

General Information

Composition
77%PP 21%PET REC 2%PU

Width
140 + 4cm

Weight
750 gr/m2 ± 5 %
1050 gr/lm ± 5 %

Custom code
UE: 5903.20.90
USA: 5903.20.18.00

Laboratory test number
IN-00663-2025-1

Specifications

Seam slippage resistance (mm)
Warp: 1,2
Weft: 1
EN ISO 13936/2:2004

Abrasion resistance (End point)
≥50.000 EN ISO 12947-2:2016

**Abrasion resistance
(change of aspect: 3000 cycles)**
3-4 EN ISO 12947/4:1998
and EN 14465:2003 (Annex A)

Pilling resistance
4-5 EN ISO 12945/2:2000

Lightfastness to weather
>6 EN ISO 105-B04:1997 (1000 hours)

Colour fastness to rubbing
Wet: 4-5
Dry: 4-5
EN ISO 105-X12:2002

**Colour fastness to domestic and
comercial laundering (30º)**
4-5 EN ISO 105-C06:1997/AC:2009

Swimming pool chlorine fastness
4-5 EN ISO 105-E03:1993

Sea water fastness
4-5 EN ISO 105-E02:1996

Care

Washing conditions

**Dimensional change domestic
washing and drying (%)**
Warp: -2%
Weft: -2%
EN ISO 3759:2008, EN ISO 6330:2000
and EN ISO 5077:2008

Bleach cleanable 80% water 20% bleach. In case of mould growth, machine-wash with a mild laundry detergent and add 0,2 liter of household bleach to the first rinse cycle. Wash at 40°C during at least 30 minutes. Use gentle cycle with minimal centrifugation.

When confectioning or washing the sofa cover with velcro please attach a protective cloth.

Ignitability

BS5852 Source 0	EN1021-Part 2:2006
EN1021-Part 1:2006	IMO Anexo 1 Parte 8
CAL TB 117:2013	Upon Request:
NFPA 260:2013	BS 7176 Low Hazard
BS5852 Source 1	UNI 9175 Clase 3IM

Environmental considerations

21%
recycled yarn

21% GRS recycled PET bottles
77% Low impact yarn (PP)
2% PU

Life cycle analysis
Cradle to gate assessment. From raw material extraction to finished fabric: resources, yarn production and dyeing, fabric weaving and finishing, waste recycling.

Carbon footprint

4,9 $kg\,CO_2\,eq/m$

Water consumption

69,7 liters/m

UNIVERSITAT POLITÈCNICA DE CATALUNYA
BARCELONATECH
Escola Superior d'Enginyeries Industrial, Aeroespacial i Audiovisual de Terrassa

Study realized in collaboration with UPC

Methodology:
Life Cycle Analysis. ISO 14040 standard.

Database:
Own data, Ecoinvent 3.6 database and published data.

Functional unit:
1 linear meters, 140 cm width.

Calculation methodology:
ReCiPe Midpoint (H) 2016 v1.0
ReCiPe Endpoint (H) 2016 v1.04
IPCC 2013 GWP 100a v1.03

**Designed and Crafted
in Terrassa (Barcelona)**

Certificates