


5 years guarantee

General Information	Specifications	Care
 Composition 47%PES 35%PP 13%PES REC 3%CO REC 2%OF REC Width 140 + 4cm Weight 692 gr/m2 ± 5 % 970 gr/lm ± 5 % Custom code UE: 5801.36.00 USA: 5801.36.00.20 Laboratory test number IN-03198-2023-1 / IN-03390-2023-1	Seam slippage resistance (mm) Warp: 2,3 Weft: 2,9 EN ISO 13936/2:2004 Abrasion resistance (End point) >100.000 EN ISO 12947-2:2016 Pilling resistance 4-5 EN ISO 12945/2:2000 Lightfastness >6 EN ISO 105-B02:1998 and 105 B02/A01:2002 Colour fastness to rubbing Dry: 4-5 Wet: 4-5 EN ISO 105-X12:2002	PERFORMANCE+ Easy to clean, longlasting fabrics Washing conditions  Soiling and cleanability 4 FORD FLTМ BN 112-08:2005 Dimensional change domestic washing and drying (%) Warp: -3 Weft: -3 EN ISO 3759:2008, EN ISO 6330:2000 and EN ISO 5077:2008 When confectioning or washing the sofa cover with veloro please attach a protective cloth. Ignitability BS5852 Source 0 EN1021-Part 1:2006 CAL TB 117:2013 NFPA 260:2013 Upon Request: BS5852 Source 1 EN1021-Part 2:2006 BS 7176 Low Hazard UNI 9175 Clase 3IM

Environmental considerations

 18% recycled yarn 13% GRS recycled PET bottles 3% Recycled CO 2% Circular yarn from own waste 35% Low impact yarn (PP) 47% PES	Life cycle analysis Cradle to gate assessment. From raw material extraction to finished fabric: resources, yarn production and dyeing, fabric weaving and finishing, waste recycling. Carbon footprint 6,45 kg CO₂ eq / m Water consumption 123,9 liters / m	 UNIVERSITAT POLITÈCNICA DE CATALUNYA BARCELONATECH Escola Superior d'Enginyeries Industrial, Aeroespacial i Audiovisual de Terrassa Study realized in collaboration with UPC Methodology: Life Cycle Analysis. ISO 14040 standard. Functional unit: 1 linear meters, 140 cm width. Database: Own data, Ecoinvent 3.6 database and published data. Calculation methodology: Aware V1.02 ReCiPe Midpoint (H) 2016 v1.04 ReCiPe Endpoint (H) 2016 v1.04 IPCC 2013 GWP 100a v1.03 Software: SimaPro 9.4.0.1
---	---	--

Designed and Crafted
in Terrassa (Barcelona)

